


TENSIONE DI RETE - TENSIONE COSTANTE 24 Vdc / MAIN VOLTAGE - CONSTANT LOW VOLTAGE 24 Vdc

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	Rif. schema Scheme diagram
	PSU.0005.0	90÷264 V 30 W 50/60 Hz	200 g (7.05 oz) 160x46x30 mm (6,299x1,811x1,181 in)	IP20 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0006.0	90÷264 V 60 W 50/60 Hz	410 g (14.46 oz) 182x62x35 mm (7,165x2,44x1,377 in)	IP20 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0020.0	220÷240 V 70 W 50/60 Hz	290 g (10.22 oz) 225x60x36 mm (8,858x2,362x1,417 in)	IP20 - CE KEMA KEUR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0007.0	90÷264 V 96 W 50/60 Hz	520 g (18.34 oz) 201x71x35 mm (7,913x2,795x1,377 in)	IP20 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0012.0	88÷264 V 120 W 50/60 Hz	650 g (22.92 oz) 125x114x40 mm (4,921x4,488x1,574 in) guida DIN / DIN rail	IP20 - CE UL - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0017.0	220÷240 V 150 W 50/60 Hz	320 g (11.28 oz) 240x61x49 mm (9,448x2,401x1,929 in)	IP20 - CE KEMA KEUR SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0013.0	88÷264 V 240 W 50/60 Hz	1030 g (36.33 oz) 125x114x63 mm (4,921x4,488x2,48 in) guida DIN / DIN rail	IP20 - CE UL - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0014.0	90÷264 V 480 W 50/60 Hz	1600 g (56.43 oz) 125x129x86 mm (4,921x5,078x3,385 in) guida DIN / DIN rail	IP20 - CE UL - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0021.0	110÷305 V 320 W 50/60 Hz	1900 g (67.02 oz) 252x90x44 mm (9,921x3,543x1,732 in)	IP65 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0008.0	90÷264 V 20 W 50/60 Hz	220 g (7.76 oz) 118x35x26 mm (4,645x1,377x1,023 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0015.0	90÷305 V 40 W 50/60 Hz	440 g (15.52 oz) 162,5x42,5x32 mm (6,397x1,673x1,259 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0016.0	90÷305 V 60 W 50/60 Hz	440 g (15.52 oz) 162,5x42,5x32 mm (6,397x1,673x1,259 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0009.0	110÷295 V 96 W 50/60 Hz	1000 g (35.27 oz) 222x68x39 mm (8,74x2,677x1,535 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0010.0	110÷295 V 150 W 50/60 Hz	1000 g (35.27 oz) 222x68x39 mm (8,74x2,677x1,535 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0018.0	220÷240 V 150 W 50/60 Hz	600 g (21.16 oz) 225x65x51 mm (8,858x2,559x2,007 in)	IP67 - CE KEMA KEUR SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0011.0	110÷305 V 240 W 50/60 Hz	1300 g (45.85 oz) 244x68x39 mm (9,606x2,677x1,535 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1

TENSIONE COSTANTE 24 Vdc DIMMERABILE / CONSTANT VOLTAGE 24 Vdc DIMMABLE

	PSU.0050.0	90÷305 V 120 W PWM dimmerabile dimnable PWM	970 g (34.22 oz) 191x63x38 mm (7,519x2,48x1,496 in)	IP67 - CE cURus - ENEC SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
--	-------------------	---	---	--	---